

- 3 -

**Amendments to the Claims:**

This listing of claims will replace all prior versions, and listings, of claims in the application:

**Listing of Claims:**

1. (Currently Amended) A substantially spherical aircraft comprising an outer envelope having a leading region and a trailing region, said aircraft having buoyancy apparatus operable to maintain said aircraft aloft, propulsion and directional apparatus co-operable to conduct said aircraft; and at least one boundary layer separation suppression element operable to encourage said aircraft to proceed as conducted, said at least one boundary layer separation suppression element, during operation for forward conduct, lowering air pressure substantially adjacent said trailing region and shifting away from said leading region, a point at which airflow about said outer envelope separates therefrom.
2. (Original) The substantially spherical aircraft of claim 1 wherein said propulsion apparatus includes a pusher propeller.
3. (Original) The substantially spherical aircraft of claim 2 wherein said aircraft has a main diametral dimension, D1, and said propeller has a diameter D2, where D2 lies in the range of 10 % to 25 % of D1.
4. (Original) The substantially spherical aircraft of claim 2 wherein said pusher propeller operates between 0 and 250 r.p.m.
5. (Original) The substantially spherical aircraft of claim 2 wherein said pusher propeller has a tip speed of less than 500 ft/s.
6. (Original) The substantially spherical aircraft of claim 2 wherein said pusher propeller is driven by an electric motor.
7. (Currently amended) ~~The substantially spherical aircraft of claim 6 further including~~  
A substantially spherical aircraft comprising:  
an outer envelope having a leading region and a trailing region;

**BEST AVAILABLE COPY**

21371627.2

- 4 -

buoyancy apparatus operable to maintain said aircraft aloft;  
propulsion and directional apparatus co-operable to conduct said aircraft, said propulsion  
apparatus including a pusher propeller driven by an electric motor;  
at least one boundary layer separation suppression element operable to encourage said  
aircraft to proceed as conducted, said at least one boundary layer separation  
suppression element, during operation for forward conduct, shifting away from  
said leading region, a point at which airflow about said outer envelope separates  
therefrom; and  
an internal combustion engine and an electric generator driven thereby.

8. (Original) The substantially spherical aircraft of claim 1 wherein said aircraft has a fuel replenishment system, said fuel replenishment system being operable while said aircraft is aloft.

9. (Original) The substantially spherical aircraft of claim 1 wherein at least one of said propulsion and directional apparatus includes an internal combustion engine and a fuel replenishment system, said fuel replenishment system being operable while said aircraft is aloft.

10. (Original) The substantially spherical aircraft of claim 1 wherein said aircraft has solar cell panels.

11. (Original) The substantially spherical aircraft of claim 1 wherein said aircraft includes an electro magnetic interface member chosen from the set of electro-magnetic interface members capable of performing at least one of (a) receiving an electro-magnetic wave form; (b) sending an electro-magnetic wave form; (c) relaying an electro-magnetic wave form; and (d) reflecting an electro-magnetic wave form.

12. (Original) The substantially spherical aircraft of claim 1 wherein said aircraft includes communications equipment operable to perform at least one of (a) receiving communications signals (b) sending communications signals; (c) relaying communications signals; and (d) reflecting communications signals.

13. (Original) The substantially spherical aircraft of claim 1 wherein said aircraft includes surveillance equipment.

21371627.2

- 5 -

14. (Original) The substantially spherical aircraft of claim 13 wherein said surveillance equipment is chosen from the set of surveillance equipment consisting of at least one of (a) communications monitoring equipment; (b) thermal imaging equipment; (c) photographic equipment; and (d) radar.

15. (Original) The substantially spherical aircraft of claim 1 wherein said aircraft has a cowling, and said cowling is substantially transparent to at least radio frequency electro-magnetic waves.

16. (Original) The substantially spherical aircraft of claim 15 wherein said aircraft has, mounted within said cowling, at least one of:

(A) communications equipment operable to perform at least one of (a) receiving communications signals (b) sending communications signals; (c) relaying communications signals; and (d) reflecting communications signals; and

(B) surveillance equipment chosen from the set of surveillance equipment consisting of at least one of (a) communications monitoring equipment; (b) thermal imaging equipment; (c) photographic equipment; and (d) radar.

17. (Original) The substantially spherical aircraft of claim 15 wherein said cowling is internally pressurised relative to ambient conditions external to said aircraft.

18. (Original) The substantially spherical aircraft of claim 1 wherein said aircraft is remotely controlled.

19. (Previously presented) A substantially spherical aircraft, said substantially spherical aircraft having a weight and an internal volume, said aircraft having an outer, load-bearing envelope defining said internal volume, buoyancy apparatus operable to maintain said aircraft aloft, propulsion and directional apparatus co-operable to conduct said aircraft; said buoyancy apparatus including an inner envelope mounted within said outer, load-bearing envelope; said internal volume being maintained at an elevated pressure relative to the external, ambient pressure to maintain said substantially spherical shape of said aircraft; said inner envelope containing a buoyant lifting fluid; said inner envelope being variably inflatable to occupy a variable portion of said internal volume; and under ambient conditions at sea level on a 59° F day, when said inner envelope is inflated to as little as 70 % of said internal volume, said inner envelope provides a buoyant force at least as great as said weight, and said aircraft having at least one of:

21371627.2

- 6 -

- (A) communications equipment operable to perform at least one of (a) receiving communications signals (b) sending communications signals; (c) relaying communications signals; and (d) reflecting communications signals; and
- (B) surveillance equipment chosen from the set of surveillance equipment consisting of at least one of (a) communications monitoring equipment; (b) thermal imaging equipment; (c) photographic equipment; and (d) radar.

20. (Previously presented) A method for operating a buoyant aircraft, said method comprising the steps of:

providing an aircraft of substantially spherical shape, said aircraft having an internal volume and a weight, said aircraft including an outer, load-bearing envelope defining said internal volume; an inner, inflatable envelope housed within said internal volume, and said aircraft having a propulsion system and a directional control system;

maintaining said internal volume at an elevated pressure relative to the external, ambient pressure;

inflating said inner, inflatable envelope with a lifting fluid to a first volume sufficient to at least balance said weight, said first volume, at sea level, being less than 70 % of said internal volume; and

operating said propulsion and directional control systems to a location greater than 10,000 ft above sea level.

21. (Original) The method of claim 20 wherein said method includes the step of maintaining said aircraft in a loitering location.

22. (Previously presented) The method of claim 21 wherein said step of maintaining said aircraft in said loitering position includes the step of maintaining lateral and longitudinal position variation relative to a deviation radius of 1000 M.

23. (Original) The method of claim 22 including maintaining said aircraft at an altitude of at least 15,000 ft.

- 7 -

24. (Original) The method of claim 20 and further including at least one of the steps chosen from the set of steps consisting of:

- (A) operating as a communications platform to do at least one of (a) receiving communications signals (b) sending communications signals; (c) relaying communications signals; and (d) reflecting communications signals; and
- (B) operating as a surveillance platform to (a) monitor communications; (b) produce thermal imaging; (c) take photographs; and (d) to operate a radar.

25. (Original) The method of claim 20 including the step of controlling operation of said buoyant aircraft from a remote location.

**This Page is Inserted by IFW Indexing and Scanning  
Operations and is not part of the Official Record**

**BEST AVAILABLE IMAGES**

Defective images within this document are accurate representations of the original documents submitted by the applicant.

Defects in the images include but are not limited to the items checked:

- ☐ BLACK BORDERS
- ☐ IMAGE CUT OFF AT TOP, BOTTOM OR SIDES
- ☐ FADED TEXT OR DRAWING
- ☐ BLURRED OR ILLEGIBLE TEXT OR DRAWING
- ☐ SKEWED/SLANTED IMAGES
- ☐ COLOR OR BLACK AND WHITE PHOTOGRAPHS
- ☐ GRAY SCALE DOCUMENTS
- ☒ LINES OR MARKS ON ORIGINAL DOCUMENT
- ☐ REFERENCE(S) OR EXHIBIT(S) SUBMITTED ARE POOR QUALITY
- ☐ OTHER: \_\_\_\_\_

**IMAGES ARE BEST AVAILABLE COPY.**

**As rescanning these documents will not correct the image problems checked, please do not report these problems to the IFW Image Problem Mailbox.**